

A gorgeous space created with nature




It has united the toughness of ceramic tiles with modern technological advances and customer aspiration to produce a range that is vast in choice. With over a decade experience in this field and in depth knowledge of markets both in India and abroad, the promoters have set up a world class integrated production facility to manufacture and supply high quality ceramic tiles. The designs, size, colours and surface finishes will be made keeping in mind the needs of the Indian as well as overseas consumers. Over the years, the company has built a solid customer base and a reputation both for itself and its product. Trust, quality and reliability have been the watchwords of the company plan to continue fulfilling the expectation of their vast array of customers. Total customer satisfaction via adoption of Quality Management Systems in all spheres of activity guarantee adherence to pre-decided standards. The company nurtures each relationship be it with the trade, consumers or suppliers. This has established as a reliable and trust worthy entity capable of overcoming market challenges.

## PUNCH- RUSTIC SERIES

12 MM THICKNESS

An elegant style for your taste




12 MM THICKNESS






2001- R PUNCH






2014- R PUNCH

12 MM THICKNESS







2004- LT PUNCH



2002- DK PUNCH



2004- DK PUNCH



12 MM THICKNESS





12 MM THICKNESS



#### PUNCH- RUSTIC SERIES

400X400 MM


12 MM THICKNESS




2010- LT PUNCH



2010- DK PUNCH






12 MM THICKNESS



12 MM THICKNESS




12 MM THICKNESS



12 MM THICKNESS







2024- DK PUNCH


12 MM THICKNESS





2025 PUNCH 2026






2027 PUNCH 2028 PUNCH

## PUNCH- ROUND SERIES

12 MM THICKNESS


An
elegant
style for
your taste




## **PUNCH- ROUND** SERIES 400X400 MM

12 MM THICKNESS





2101 PUNCH





2104 PUNCH

#### PUNCH- ROUND SERIES


400X400 MM

12 MM THICKNESS





2105 PUNCH







2108 PUNCH

2109 PUNCH




#### PUNCH- ROUND SERIES

400X400 MM

12 MM THICKNESS








2111 PUNCH



2112 PUNCH



2114 PUNCH



#### **PUNCH- ROUND** SERIES

400X400 MM

12 MM THICKNESS



2115 PUNCH




2116 PUNCH

## PUNCH- LINER SERIES

12 MM THICKNESS


An elegant style for your taste



12 MM THICKNESS



2201- LT PUNCH




2202- DK PUNCH




2201- DK PUNCH

12 MM THICKNESS




2204- LT PUNCH



2204- DK PUNCH



12 MM THICKNESS




PUNCH


2211


**PUNCH** 

HEAVY DUTY
OUTDOOR TILES




12 MM THICKNESS







2214 PUNCH

12 MM THICKNESS





2215 PUNCH







2218 PUNCH

2219 PUNCH

12 MM THICKNESS




2220 PUNCH



2221 PUNCH

12 MM THICKNESS






2224 PUNCH






2227 PUNCH 2228 PUNCH

12 MM THICKNESS







**PUNCH** 


HEAVY DUTY
OUTDOOR TILES



12 MM THICKNESS







12 MM THICKNESS



#### TECHNICAL SPECIFICATIONS

CHARACTERISTIC	STANDARD AS PER ISO-13006/EN 14411 GROUP Bla	MEAN VALUE OF POLISHED GVT	MEAN VALUE OF GVT / PGVT	TEST METHOD				
REGULATORY PROPERTIES								
Deviation in length & width	±0.5 %	±0.1 %	±0.1 %	ISO-10545-2				
Deviation in thickness	±5.0 %	±4.0 %	±4.0 %	ISO-10545-2				
Straightness in side	±0.5 %	±0.1 %	±0.1 %	ISO-10545-2				
Rectangularity	±0.5 %	±0.1 %	±0.1 %	ISO-10545-2				
Surface flatness	±0.5 %	±0.2 %	±0.2 %	ISO-10545-2				
Color dierence	Unaltered	No change	No change	ISO-10545-16				
Glossiness	As per mfg	Min 90%	Min 4%	GLOSSOMETER				
STRUCTURAL PROPERTIES								
Water absorption	< 0.50 %	< 0.20 %	< 0.20 %	ISO-10545-3				
Apparent density	> 2.0 g/cc	>2.10 g/cc	>2.10 g/cc	DIN 51082				
MASSIVE MECHANICAL PROPERTIES								
	Min. 35 N/mm	Min. 40 N/mm²	Min. 40 N/mm²	ISO-10545-4				
Breaking strength	Min. 1300 N	Min. 2000 N	Min. 2000 N	ISO-10545-4				
Impact resistance	As per mfg	Min. 0.55	Min. 0.55	ISO-10545-5				
SURFACE MECHANICAL PROPERTIES								
Surface abrasion resistance	As per mfg	Min. Class-3	Min. Class-4	ISO-10545-7				
MOH's hardness	As per mfg	Min. 4	Min. 5	EN 101				
THERMO HYDROMETRIC PROPERTIES								
Frost resistance	No damage	No damage	No damage	ISO-10545-12				
Thermal shock resistance	No damage	No damage	No damage	ISO-10545-9				
Moisture expansion	Nil	Nil	Nil	ISO-10545-10				
Thermal expansion (COE)	Max. 9.0 x 10 <sup>-6</sup>	Max. 6.5x10 <sup>-6</sup>	Max. 6.5 x 10 <sup>-6</sup>	ISO-10545-8				
Crazing resistance	As per mfg.	Min. 10 Cycle	Min. 10 Cycle	ISO-10545-11				
CHEMICAL PROPERTIES								
Chemical resistance	No damage	No damage	No damage	ISO-10545-13				
Stain resistance	Resistant	Resistant	Resistant	ISO-10545-14				
SAFETY PROPERTIES								
Slip resistance	As per mfg.	>0.40	>0.40	ISO-10545-17				
Fire resistance	As per mfg.	Fire proof	Fire proof	N. A.				
Lead & Cadmium given o by glazed tiles	As per mfg.	Does not yield Pb & Cd	Does not yield Pb & Cd	ISO-10545-15				

#### **Packing Details**

SR. NO.	SIZE ( IN MM)	PACKING	COVERAGE AREA	Thickness	WEIGHT
1	400X400MM	5 PIS	0.80SQ.MTR./8.61 SQ.FT.	12MM	19 Kg Approx

Note: •Colour Shown are as accurate as the limitations of the printing process will allow. • Prospective customers are advised to inspect a sample of the tile before ordering. • Every effort has been made to ensure the accuracy of the information given. • However, the company reserve the right to change the specifications without prior notice. • Sometime variations in shade or size being inherent to ceramic industry may occur. • Before fixing, we advise you to follow the fixing instructions on the cartons of the tiles as no responsibility can be accepted by the company once the tiles have been fixed.

#### **Applications**

























DISCLAIMER: We reserves the right to delete & amend either totally of partially, and of the colours, shapes, size, references and other technical specification contain in catalogue at any time, the colours shown of tiles in this catalogue are purely illustrative and limited to printing process. Please refer actual sample final selection. The details of colours, size, references should be vitrified for Typographical errors. SHADE & SIZE VARIATIONS are inherent characteristics of ceramics. NO COMPLIANT SHALL BE SHALL ENTERTAINED ON TILES ALREADY LAID/FIXED.

